Department of Energy Advanced Manufacturing Office EnPI V4.0 Tool Algorithm

Updated September 11th, 2014

Contents

Definition of Symbols	3
Facility Level Calculations	4
Calculation Methods when Actual Values are used	4
Energy Intensity (MMBtu/Unit of Production or MMBtu/sq ft)	4
Cumulative Improvement (Total Change) in Energy Intensity from Baseline Year (%)	4
Annual Improvement (Annual Change) in Energy Intensity for Current Year (%)	4
Annual Savings (Total Energy Savings) since Baseline Year (MMBtu/year)	4
New Energy Savings for Current Year (MMBtu/year)	4
Estimated Annual Cost Savings (\$/year)	4
Calculation Method when Normalized Values are used	6
SEnPI (unitless)	6
Cumulative Improvement (Total Change) in Energy Intensity from Baseline Year (%)	6
Annual Improvement (Annual Change) in Energy Intensity for Current Year (%)	7
Annual Savings (Total Energy Savings) since Baseline Year (MMBtu/year)	7
New Energy Savings for Current Year (MMBtu/year)	8
Estimated Annual Cost Savings (\$/year)	8
SEP CUSUM (MMBtu)	9
Corporate Level Calculations	9
Current Year Total Primary Energy Use (MMBtu/year)	9
Adjustment for Baseline Primary Energy (MMBtu/year)	9
Adjusted Baseline Primary Energy (MMBtu/year)	9
Cumulative Improvement (Total Change) in Energy Intensity from Baseline Year (%)	9
Annual Improvement (Annual Change) in Energy Intensity for Current Year (%)	9
Annual Savings (Total Energy Savings) since Baseline Year (MMBtu/year)	9
New Energy Savings for Current Year (MMBtu/year)	9
Least Squares Regression Analysis	10

Definition of Symbols

The following symbols and abbreviations are used in the *Facility Level Calculations* and *Corporate Level Calculations* sections of the document.

AI Annual Improvement (Annual change) in Energy Intensity for Current Year

(%)

BY Baseline Year

Energy Cost_P Energy cost for a given time interval (e.g. day, week or month)

CI Cumulative Improvement (Total Change) in Energy Intensity from Baseline

Year (%)

CS Energy Cost Savings

CY Current Year

Corp Corporate level total

EC Modeled Source (Primary) Energy Consumption (MMBtu)

EC Actual Source (Primary) Energy Consumption (MMBtu)

EI Energy Intensity or Energy Normalized for Relevant Factors (MMBtu/ Unit of

Production or MMBtu/sq ft)

Energy Savings i The energy savings for a given time interval (e.g. day, week, or month)

MY Model Year

N Number of plants within the company

I Interval of time in which the data is entered (e.g. daily, weekly, monthly, etc.)

PY Previous Year

SEnPI Superior Energy Performance Indicator

Unit Cost Unit energy cost

Facility Level Calculations

The following section describes the calculation methods used for the facility level calculations.

Calculation Methods when Actual Values are used

When "Use Actual" is selected as the calculation method in the EnPI tool, the following calculations are used.

Energy Intensity (MMBtu/Unit of Production or MMBtu/sq ft)

$$Production \ EI_{CY} = \frac{EC}{Total \ Production}$$

$$Building \; EI_{CY} = \frac{EC}{Total \; Building \; Square \; Footage}$$

Cumulative Improvement (Total Change) in Energy Intensity from Baseline Year (%)

When using Production Energy Intensity:

$$CI_{CY} = \frac{(Production EI_{BY} - Production EI_{CY})}{Production EI_{BY}}$$

When using Building Energy Intensity:

$$CI_{CY} = \frac{\left(Building\ EI_{BY} - Building\ EI_{CY}\right)}{Building\ EI_{BY}}$$

Annual Improvement (Annual Change) in Energy Intensity for Current Year (%)

$$AI_{BY} = CI_{CY} - CI_{PY}$$

Annual Savings (Total Energy Savings) since Baseline Year (MMBtu/year)

The following equation is used to calculate the savings for each energy type (e.g. electric, natural gas, etc.) and for the total of all the energy sources entered into the tool.

Annual Savings_{CY} =
$$EC_{BY} - EC_{CY}$$

New Energy Savings for Current Year (MMBtu/year)

New Energy Savings_{CY} = Annual Savings_{CY} - Annual Savings_{PY}

Estimated Annual Cost Savings (\$/year)

First, the unit cost for each energy type (e.g. electric, natural gas, etc.) for each time interval is calculated by dividing the energy cost by the energy consumption.

$$Unit\ Cost_i = \frac{Energy\ Cost_i}{EC_i}$$

Next, the daily, weekly or monthly energy savings is calculated for each energy type by subtracting the current year consumption for the time interval from the baseline year consumption for the same time interval [e.g. September 2010 (baseline) electric - September 2013 (current year) electric].

Energy Savings_i =
$$EC_{RYi} - EC_{CYi}$$

The unit cost for each energy type and time interval is then multiplied by the energy savings for each energy type and time interval.

$$CS_i = Unit\ Cost_i \times Energy\ Savings_i$$

Finally, the cost savings for each energy type (e.g. electric, natural gas, etc.) and time period is summed to determine the annual cost savings.

Annual Cost Savings =
$$\sum_{i=1}^{N} CS_{Electric\ i} + \sum_{i=1}^{N} CS_{Natural\ Gas\ i} + \sum_{i=1}^{N} CS_{Energy\ type\ X\ i}$$

Calculation Method when Normalized Values are used

When "Regression Analysis" is selected as the calculation method in the EnPI tool, the following calculations are used.

SEnPI (unitless)

Forecasting (Model year = baseline year)

Calculation for the model year:

$$SEnPI_{MY} = 1$$

Calculation for all years after the model year:

$$SEnPI_{CY} = \frac{EC_{CY}}{\widehat{EC}_{CY}}$$

Chaining (Model year does not = baseline year, and does not = last reporting year)

Calculation for all years prior to the model year, including the baseline year:

$$SEnPI_{CY} = \frac{\widehat{EC}_{CY}}{EC_{CY}}$$

Calculation for the model year:

$$SEnPI_{MY} = 1$$

Calculation for all years after the model year:

$$SEnPI_{CY} = \frac{EC_{CY}}{EC_{BY}} \times \frac{\widehat{EC}_{BY}}{\widehat{EC}_{CY}}$$

Backcasting (Model year = last reporting year)

Calculation for all years prior to the model year, including the baseline year:

$$SEnPI_{CY} = \frac{\widehat{EC}_{CY}}{EC_{CY}}$$

Calculation for the model year:

$$SEnPI_{MY} = 1$$

Cumulative Improvement (Total Change) in Energy Intensity from Baseline Year (%)

Forecasting (Model year = baseline year)

$$CI_{CY} = (1 - SEnPI_{CY}) \times 100$$

Chaining (Model year does not = baseline year, and does not = last reporting year)

Calculation for the model year, and all years prior to the model year:

$$CI_{CY} = \{ [(1 - SEnPI_{PY}) - (1 - SEnPI_{CY})] \times 100 \} + CI_{PY}$$

Calculation for all years after the model year:

$$CI_{CY} = (1 - SEnPI_{CY}) \times 100$$

Backcasting (Model year = last reporting year)

$$CI_{CY} = \{ [(1 - SEnPI_{PY}) - (1 - SEnPI_{CY})] \times 100 \} + CI_{PY}$$

Annual Improvement (Annual Change) in Energy Intensity for Current Year (%)

Forecasting (Model year = baseline year)

$$AI_{CY} = CI_{CY} - CI_{PY}$$

Chaining (Model year does not = baseline year, and does not = last reporting year)

Calculation for the model year, and all years prior to the model year:

$$AI_{CY} = [(1 - SEnPI_{PY}) - (1 - SEnPI_{CY})] \times 100$$

Calculation for all years after the model year:

$$AI_{CY} = CI_{CY} - CI_{PY}$$

Backcasting (Model year = last reporting year)

$$AI_{CY} = [(1 - SEnPI_{PY}) - (1 - SEnPI_{CY})] \times 100$$

Annual Savings (Total Energy Savings) since Baseline Year (MMBtu/year)

The following equations are used to calculate the savings for each energy type (e.g. electric, natural gas, etc.) and for the total of all the energy sources entered into the tool.

Forecasting (Model year = baseline year)

Annual Savings_{CY} =
$$\widehat{EC}_{CY}$$
 – EC_{CY}

Chaining (Model year does not = baseline year, and does not = last reporting year)

Calculation for the model year, and all years prior to the model year:

Annual Savings_{CY} = Annual Savings_{PY} +
$$\left[\left(EC_{PY} - \widehat{EC}_{PY}\right) - \left(EC_{CY} - \widehat{EC}_{CY}\right)\right]$$

Calculation for all years after the model year:

Annual Savings_{CY} =
$$\widehat{EC}_{CY}$$
 – EC_{CY}

Backcasting (Model year = last reporting year)

$$Annual\ Savings_{CY} = Annual\ Savings_{PY} + \left[\left(EC_{PY} - \widehat{EC}_{PY} \right) - \left(EC_{CY} - \widehat{EC}_{CY} \right) \right]$$

New Energy Savings for Current Year (MMBtu/year)

New Energy Savings_{CY} = Annual Savings_{CY} - Annual Savings_{PY}

Estimated Annual Cost Savings (\$/year)

First, the unit cost for each energy type (e.g. electric, natural gas, etc.) for each time interval is calculated by dividing the energy cost by the energy consumption.

$$Unit\ Cost_i = \frac{Energy\ Cost_i}{EC_i}$$

Next, the daily, weekly or monthly energy savings is calculated for each energy type and time interval using the equations below. In the equations below, the subscript "i" denotes the current time interval (e.g. day, week or month). The subscript "i-1" indicates the previous time interval. For example, if "i" is referencing September 2013, "i-1" indicates August 2013.

Forecasting (Model year = baseline year)

Energy Savings_i =
$$\widehat{EC_i} - EC_i$$

Chaining (Model year does not = baseline year, and does not = last reporting year)

Calculation for the model year, and all years prior to the model year:

Energy Savings_i = Energy Savings_{i-1} +
$$[(EC_{i-1} - \widehat{EC}_{i-1}) - (EC_i - \widehat{EC}_i)]$$

Calculation for all years after the model year:

Energy Savings_i =
$$\widehat{EC_i}$$
 – EC_i

Backcasting (Model year = last reporting year)

Energy Savings_i = Energy Savings_{i-1} +
$$[(EC_{i-1} - \widehat{EC}_{i-1}) - (EC_i - \widehat{EC}_i)]$$

The unit cost for each energy type and time interval is then multiplied by the energy savings for each energy type and time interval.

$$CS_i = Unit\ Cost_i \times Energy\ Savings_i$$

Finally, the cost savings for each energy type (e.g. electric, natural gas, etc.) and time period is summed to determine the annual cost savings.

$$Annual\ Cost\ Savings = \sum_{i=1}^{N} CS_{Electric\ i} + \sum_{i=1}^{N} CS_{Natural\ Gas\ i} + \sum_{i=1}^{N} CS_{Energy\ type\ X\ i}$$

SEP CUSUM (MMBtu)

For all regression methods, the following equation is used to calculate CUSUM.

$$CUSUM = (EC_{Current\ Interval} - \widehat{EC}_{Current\ Interval}) + CUSUM_{Previous\ Interval}$$

In the equation above, "Interval" represents the time interval entered by the user (e.g. month, week, day). For the first data point after the model year when chaining is selected as the regression method the "previous interval" refers to the last data point before the model year.

Corporate Level Calculations

This section lists the calculations for the corporate roll up. These calculations are appropriate whether all participating plants selected "use actual", "regression analysis", or a blend of the two methods.

Current Year Total Primary Energy Use (MMBtu/year)

The following equation is used to calculate the savings for each energy type (e.g. electric, natural gas, etc.) and for the total of all the energy sources entered into the tool.

$$EC_{Corp} = EC_{Plant 1} + EC_{Plant 2} + \cdots + EC_{Plant N}$$

Adjustment for Baseline Primary Energy (MMBtu/year)

Adjustment for Baseline $EC_{CY\ Corp} = Annual\ Savings_{CY\ Corp} + EC_{CY\ Corp} - EC_{BY\ Corp}$

Adjusted Baseline Primary Energy (MMBtu/year)

Adjusted
$$EC_{BY\ Corp} = EC_{BY\ Corp} + Adjustment\ for\ Baseline\ EC_{CY\ Corp}$$

Cumulative Improvement (Total Change) in Energy Intensity from Baseline Year (%)

$$=\frac{\left[\left(\widehat{EC}_{BY\;Plant\;1}\times CI_{CY\;Plant\;1}\right)+\left(\widehat{EC}_{BY\;Plant\;2}\times CI_{CY\;Plant\;2}\right)+\cdots+\left(\widehat{EC}_{BY\;Plant\;N}\times CI_{CY\;Plant\;N}\right)\right]}{\widehat{EC}_{BY\;Plant\;1}+\widehat{EC}_{BY\;Plant\;2}+\cdots+\widehat{EC}_{BY\;Plant\;N}}$$

*When a plant that selects "use actual" as the calculation method is included in the roll-up, $EC_{BY\ Plant}$ should be used in place of $\widehat{EC}_{BY\ Plant}$.

Annual Improvement (Annual Change) in Energy Intensity for Current Year (%)

$$AI_{CY\ Corp} = CI_{CY\ Corp} - CI_{PY\ Corp}$$

Annual Savings (Total Energy Savings) since Baseline Year (MMBtu/year)

New Energy Savings for Current Year (MMBtu/year)

New Energy Savings_{CY Corp} = Annual Savings_{CY Corp} - Annual Savings_{PY Corp}

Least Squares Regression Analysisⁱ

This section outlines the equations that are used for the regression analysis in the EnPI tool. The tool uses a Microsoft Excel add-in to perform the regression analysis. The add-in uses the equations listed below to predict the energy consumption based on the independent variables entered by the user.

Regression analysis is a statistical method for predicting the behavior of a dependent variable based on the independent variables. The table below defines the symbols that will be used in the regression analysis equations outlined in this section.

Equation Symbols and Definitions

Symbol	Definition
у	Dependent variable predicted by the regression model (i.e.
	predicted energy use)
y*	Measured dependent variable (i.e. measured energy use)
p	Number of independent variables and coefficients
x _i (i=1, 2 p)	The ith independent variable from total set of p variables (i.e.
	production, HDD, CDD, etc.)
b _i (i=1, 2 p)	The ith coefficient corresponding to x _i
b_0	Intercept or constant
k=p+1	Total number of parameters including intercept
n	Number of observations
i=1, 2 p	Independent variables' index
j=1, 2n	Data points index
\mathbb{R}^2	Coefficient of determination
r	Residual (or error, or deviation)
SSE	Residual (error) sum of squares (or regression sum of
	squares)
SS_R	Regression sum of squares
SS_T	Total sum of squares

For the EnPI tool, the dependent variable is the energy consumption by the facility. The independent variables can be production, cooling degree days (CDD), heating degree days (HDD), etc. If the user selects more than one independent variable, a multivariable linear regression equation is needed to predict the dependent variable or energy consumption at the facility.

Regression analysis determines the formula that can be used to predict the dependent variable based on the independent variables. The general formula for a multiple linear model is:

$$y = b_0 + b_1 x_1 + b_2 x_2 + \dots b_p x_p$$

In this formula, y is the predicted dependent variable. The measured dependent variable is depicted by the y*. The difference between the predicted and measured dependent variable is called the residual (also known as error or deviation).

$$r_j = y_j^* - y_j$$

The goal of regression analysis is to determine the coefficients $(b_{1, 2... i})$ that result in a minimized error sum of squares. The error sum of squares (SSE) is calculated by:

$$SS_E = \sum_{j}^{n} (r_j - r_{avg})^2$$

Microsoft Excel calculates the error sum of squares (SS_E) for each combination of coefficients and determines the combination of coefficients that minimize the SS_E . The coefficients that result in the lowest error sum of squares are entered into the regression model to produce an equation that can be used to estimate the dependent variable given the independent variable(s).

Along with determining the model that best predicts the relationship between the independent and dependent variables, Microsoft Excel also calculates the coefficient of determination. The coefficient of determination (R^2) is a measure of how well future outcomes are likely to be predicted by the model. A regression model is a good fit for the data if the R^2 value is close to 1. In order to calculate the R^2 value, the regression sum of squares (SS_R) and the total sum of squares (SS_T) first need to be defined. The regression sum of squares is defined as:

$$SS_R = \sum_{j=1}^{n} (y_j - y *_{avg})^2$$

And the total sum of squares is calculated using the following equation:

$$SS_T = \sum_{j=1}^{n} (y *_j - y *_{avg})^2$$
, where $y *_{avg} = (\sum_{j=1}^{n} y *_j)/n$

The total sum of squares can also be defined:

$$SS_T = SS_E + SS_R$$

Now that the residual, regression, and total sum of squares have been defined, the coefficient of determination can be defined as:

$$R^2 = \frac{SS_R}{SS_T} = 1 - SS_E/SS_T$$

Source: Cameron, Colin. "Excel 2007: Multiple Regression." *UC-Davis Economics*. University of California Davis Department of Economics, n.d. Web. 3 Oct 2012. http://cameron.econ.ucdavis.edu/excel/ex61multipleregression.html>.