

BUILDING TECHNOLOGIES OFFICE

Tax Deduction Qualified Software for buildings placed in service on or after January 1, 2016.

OpenStudio 2.3.0 with EnergyPlus 8.8.0

On this page you'll find information about the Open Studio 2.3.0 with EnergyPlus 8.8.0 Qualified Software for Calculating Commercial Building Tax Deductions | Department of Energy http://energy.gov/eere/buildings/qualified-software-calculating-commercial-building-tax-deductions, which calculates energy and power cost savings that meet federal tax incentive requirements for commercial buildings.

Date Documentation Received by DOE: November 11, 2017

Statements and information in the right hand column of this table are from the software developer.

Internal Revenue Code §179D (c)(1) and (d) Regulations Notice 2006-52, Section 6 requirements as amplified by Notice 2008-40, Section 4 requirements.	
(1) The name, address, and (if applicable) web site of the software developer;	Amir Roth Technology Manager, Building Energy Modeling Office of Building Technologies, EE-2J U.S. Department of Energy 1000 Independence Avenue, SW Washington, CD 20585-0121 http://energyplus.net
(2) The name, email address, and telephone number of the person to contact for further information regarding the software;	Amir Roth Amir.roth@ee.doe.gov 202-287-1694
(3) The name, version, or other identifier of the software as it will appear on the list;	OpenStudio, Version 2.3.0 with EnergyPlus, Version 8.8.0
(4) All test results, input files, output files, weather data, modeler reports, and the executable version of the software with which the tests were conducted; and	Provided to DOE
(5) A declaration by the manager in charge of software development, made under penalties of perjury, that all statements and information in the right hand column of this table are true and correct.	On behalf of the <i>EnergyPlus software</i> development team I certify the following:
(a) The software has been tested according to ANSI/ASHRAE Standard 140-2014 Standard Method of Test for the Evaluation of Building Energy Analysis Computer Programs (except for sections 5.2.4, 7, and 8);	The software has been tested according to the American National Standards Institute/American Society of Heating, Refrigerating and Air-Conditioning Engineers (ANSI/ASHRAE) Standard 140-2014 Standard Method of Test for Evaluation of Building Energy Analysis Computer Programs.
(b) The software can model explicitly ⁽¹⁾ —	The EnergyPlus software is fully compliant with ASHRAE 90.1-2007 and meets all of the below requirements.

(i) 8,760 hours per year;	The EnergyPlus software complies.
(ii) Calculation methodologies for the building components being modeled;	The EnergyPlus software complies.
(iii) Hourly variations in occupancy, lighting power, miscellaneous equipment power, thermostat setpoints, and HVAC system operation, defined separately for each day of the week and holidays;	The EnergyPlus software complies.
(iv) Thermal mass effects;	The EnergyPlus software complies.
(v) Ten or more thermal zones;	The EnergyPlus software complies.
(vi) Part-load performance curves for mechanical equipment;	The EnergyPlus software complies.
(vii) Capacity and efficiency correction curves for mechanical heating and cooling equipment; and	The EnergyPlus software complies.
(viii) Air-side and water-side economizers with integrated control.	The EnergyPlus software complies.
$(c)^{(2)}$ The software can explicitly model each of the following HVAC systems listed in Appendix G of Standard 90.1-2007 ⁽¹⁾ :	
(i) Packaged Terminal Air Conditioner(PTAC), constant volume (CV) fan, DX coil cooling, hot-water fossil fuel boiler.	The EnergyPlus software models this system.
(ii) Packaged Terminal Heat Pump (PTHP), CV fan, DX coil cooling, electric heat pump heating.	The EnergyPlus software models this system.
(iii) Packaged Rooftop Air Conditioner (PSZ-AC), CV fan, DX coil cooling, fossil fuel furnace heating.	The EnergyPlus software models this system.
(iv) Packaged Rooftop Heat Pump (PSZ-HP), CV fan, DX coil cooling, electric heat pump heating.	The EnergyPlus software models this system.
(v) Packaged Rooftop Variable-Air-Volume(PVAV) with reheat, Variable-Air-Volume(VAV) fans, DX coil cooling, hot-water fossil fuel boiler.	The EnergyPlus software models this system.
(vi) Packaged VAV with parallel fan- powered boxes (PVAV with PFP boxes) with reheat, VAV fans, DX coil cooling, electric resistance heating.	The EnergyPlus software models this system.

(vii) Packaged Rooftop VAV with reheat, VAV fans, chilled water cooling, hot-water fossil fuel boiler.	The EnergyPlus software models this system.	
(viii) VAV with PFP boxes with reheat, VAV fans, chilled water cooling, electric resistance heating.	The EnergyPlus software models this system.	
(d) The software can—		
(i) Either directly determine energy and power costs or produce hourly reports of energy use by energy source suitable for determining energy and power costs separately; and	The EnergyPlus software complies.	
(ii) Design load calculations to determine required HVAC equipment capacities and air and water flow rates.	The EnergyPlus software complies.	
(e) ⁽²⁾ The software can explicitly model:		
(i) Natural ventilation.	The EnergyPlus software models natural ventilation.	
(ii) Mixed mode (natural and mechanical) ventilation.	The EnergyPlus software models mixed mode ventilation.	
(iii) Earth tempering of outdoor air.	The EnergyPlus software models earth tempering of outdoor air.	
(iv) Displacement ventilation.	The EnergyPlus software models displacement ventilation	
(v) Evaporative cooling.	The EnergyPlus software models evaporative cooling.	
(vi) Water use by occupants for cooking, cleaning or other domestic uses.	The EnergyPlus software models water use by occupants	
(vii) Water use by heating, cooling, or other equipment, or for on-site landscaping.	The <i>EnergyPlus software</i> models water use by heating, cooling, and other equipment as well as for on- site landscaping.	
(viii) Automatic interior or exterior lighting controls (such as occupancy, photocells, or time-clocks).	The EnergyPlus software models automatic interior and exterior lighting controls.	
(ix) Daylighting (sidelighting, skylights, or tubular daylight devices).	The EnergyPlus software models sidelighting, skylights, and tubular daylighting devices.	
(x) Improved fan system efficiency through static pressure reset.	The EnergyPlus software models improved fan system efficiency through static pressure reset.	



	The <i>EnergyPlus software</i> models low and high temperature radiant heating and cooling.
(xii) Multiple or variable-speed control for fans, cooling equipment, or cooling towers.	The <i>EnergyPlus software</i> models multiple and variable-speed control for fans, cooling equipment, and cooling towers.
combined heat and power systems, fuel	The <i>EnergyPlus software</i> models on-site energy systems including combined heat and power, photovoltaic systems, and solar water and air systems.

Date Posted: November 11, 2017

- 1) 90.1-2007 is defined by the PATH Act of 2015 as "Standard 90.1-2007 of ASHRAE and IESNA (as in effect on the day before the date of the adoption of Standard 90.1-2010 of such Societies)." This definition includes 90.1-2007 and the addenda supplement package (Addenda a, b, c, g, h, i, j, k, l, m, n, p, q, s, t, u, w, y, ad, and aw) and addendum r, plus all published errata.
- 2) Software that cannot explicitly model one or more of the HVAC systems or features in sections 5.c and 5.e of the table can still be listed as qualified software. It cannot, however, be used for 179D analyses of projects that need to model such systems or features. When this is the case, the statement used for the particular requirements shall be as follows: The *EnergyPlus software* cannot model system or feature X and shall not be used for projects with this technology.

Tax Deduction Qualified Software — http://energy.gov/eere/buildings/qualified-software-calculating-commercial-building-tax-deductions

Amir Roth

Technology Manager, Building Energy Modeling